



SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

1 Identification of the Substance/Mixture and Company

Product Name: EasyCut Decal Solution

SDS Code: SSDCECD

Product Description: Bone Decalcifier

Manufacturer/Supplier:

StatLab Medical Products
2090 Commerce Drive
McKinney, TX 75069
800-442-3573
www.statlab.com

Emergency Telephone Number: CHEMTREC 800-424-9300 (USA & Canada)
CHEMTREC 703-527-3887 (International)
Non-transport 800-225-8867 (USA)

2 Hazards Identification

Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H335 May cause respiratory irritation.

Flam. Liq. 4 H227 Combustible liquid.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labeling:

hydrogen chloride
formic acid

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution
Hazard statements

Combustible liquid.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Do not breathe dusts or mists.

Wear protective gloves / eye protection / face protection.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NEPA ratings (scale 0 - 4)

Health = 3

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 3

Fire = 0

Reactivity = 0

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.**vPvB:** Not applicable.

3 Composition

Chemical characterization: Mixtures
Description: Mixture of the substances listed below with nonhazardous additions.
Dangerous components:

64-18-6	formic acid	<25%
7647-01-0	hydrogen chloride	<25%

4 First Aid Measures

Description of first aid measures
General information: Immediately remove any clothing soiled by the product.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.**Information for doctor:****Most important symptoms and effects, both acute and delayed:** No further relevant information available.**Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Firefighting Measures

Extinguishing media**Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**Special hazards arising from the substance or mixture:**

During heating or in case of fire poisonous gases are produced.

Advice for firefighters**Protective equipment:** Mouth respiratory protective device.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

Handling:**Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution
Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:	
64-18-6 formic acid	
PEL	Long-term value: 9 mg/m ³ , 5 ppm
REL	Long-term value: 9 mg/m ³ , 5 ppm
TLV	Short-term value: 19 mg/m ³ , 10 ppm Long-term value: 9.4 mg/m ³ , 5 ppm
7647-01-0 hydrogen chloride	
PEL	Ceiling limit value: 7 mg/m ³ , 5 ppm
REL	Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV	Ceiling limit value: 2.98 mg/m ³ , 2 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls:
Personal protective equipment:
General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution
Eye protection: Tightly sealed goggles

9 Physical and Chemical Properties

Information on basic physical and chemical properties

General Information

Appearance

Form:	Liquid
Color:	Colorless
Odor:	Mildly acidic
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

Flash point: 71 °C (160 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 520 °C (968 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Not determined.

Explosion limits:

Lower:	14.0 Vol %
Upper:	33.0 Vol %

Vapor pressure at 20 °C (68 °F): 43 hPa (32 mm Hg)

Density: Not determined.

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Dynamic: Not determined.

Kinematic: Not determined.

Other information: No further relevant information available.

10 Stability and Reactivity

Reactivity: No further relevant information available.

Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution
Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicology Information

Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
64-18-6 formic acid

Oral	LD50	1100 mg/kg (rat)
------	------	------------------

Primary irritant effect:
On the skin: Caustic effect on skin and mucous membranes.

On the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic categories
IARC (International Agency for Research on Cancer)

7647-01-0	hydrogen chloride	3
-----------	-------------------	---

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological Information

Toxicity:
Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:
Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:
General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Results of PBT and vPvB assessment
PBT: Not applicable.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution
vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal Considerations

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport Information

UN-Number	UN3264
DOT, ADR, IMDG, IATA	
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid, Formic acid)
DOT	
ADR	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid, Formic acid)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID, FORMIC ACID)
Transport hazard class(es)	
DOT	
	
Class	8 Corrosive substances
Label	8
ADR, IMDG, IATA	
	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, ADR, IMDG, IATA	II
Environmental hazards	
Marine pollutant:	No
Special precautions for user:	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F-A,S-B
Segregation groups	Acids
Stowage Category	B

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution

Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
ADR	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID, FORMIC ACID), 8, II

15 Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture
SARA

Section 355 (extremely hazardous substances):

7647-01-0 | hydrogen chloride

Section 313 (Specific toxic chemical listings):

64-18-6 | formic acid

7647-01-0 | hydrogen chloride

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution**Carcinogenic categories****EPA (Environmental Protection Agency)**

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

7647-01-0 hydrogen chloride

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS05 GHS07

Signal word Danger**Hazard-determining components of labeling:**

hydrogen chloride

formic acid

Hazard statements

Combustible liquid.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Do not breathe dusts or mists.

Wear protective gloves / eye protection / face protection.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

This information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 08/16/2022

Supersedes Date: 09/08/2016

Revision Date 08/16/2022

Product Name: EasyCut Decal Solution

of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of the material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

Department issuing SDS: Regulatory Department**Contact:** Phone 800-442-3573**Date of preparation / last revision** 09/08/2016**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Copyright © 2019-2021 SLMP, LLC, DBA StatLab Medical Products. All Rights Reserved.

No part of these pages may be used for any purpose other than personal use. Therefore, reproduction, modification, storage in a retrieval system or retransmission, in any form or by any means, for reasons other than personal use, is strictly prohibited without prior written permission.