



SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

1 Identification of the Substance/Mixture and Company

Product Name: ClearMount Mounting Medium

SDS Code: SSMMC01

Product Description: Mounting Medium

Manufacturer/Supplier:

StatLab Medical Products
2090 Commerce Drive
McKinney, TX 75069
800-442-3573
www.statlab.com

Emergency Telephone Number: CHEMTREC 800-424-9300 (USA & Canada)
CHEMTREC 703-527-3887 (International)
Non-transport 800-225-8867 (USA)

2 Hazards Identification

Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Hazard pictograms

GHS02 GHS06 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

Xylene, Mixed Isomers
toluene

Hazard statements

Highly flammable liquid and vapor.
Toxic in contact with skin.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
Wear protective gloves / protective clothing.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Specific treatment (see on this label).
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Do NOT induce vomiting.
In case of fire: Use for extinction: CO2, powder or water spray.
Take off immediately all contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium
Classification system:**NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *2

Fire = 3

Reactivity = 0

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition

Chemical characterization: Mixtures**Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

108-88-3	toluene	<50%
	Xylene, Mixed Isomers	<50%

4 First Aid Measures

Description of first aid measures**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** If symptoms persist consult doctor.**Information for doctor:****Most important symptoms and effects, both acute and delayed:** No further relevant information available.**Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Firefighting Measures

Extinguishing media**Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**Special hazards arising from the substance or mixture:**

During heating or in case of fire poisonous gases are produced.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Advice for firefighters**Protective equipment:** Mouth respiratory protective device.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

Handling:**Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

Additional information about design of technical systems: No further data; see item 7.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium
Control parameters
Components with limit values that require monitoring at the workplace:
108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

Xylene, Mixed Isomers

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Ingredients with biological limit values:
108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

Xylene, Mixed Isomers

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls:
Personal protective equipment:
General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

9 Physical and Chemical Properties

Information on basic physical and chemical properties
General Information
Appearance

Form:	Liquid
Color:	Colorless
Odor:	Aromatic
Odor threshold:	Not determined.

pH-value:	Not determined.
------------------	-----------------

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	110 °C (230 °F)

Flash point:	4 °C (39 °F)
---------------------	--------------

Flammability (solid, gaseous):	Not applicable.
---------------------------------------	-----------------

Ignition temperature:	535 °C (995 °F)
------------------------------	-----------------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Auto igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
-----------------------------	--

Explosion limits:

Lower:	1.2 Vol %
Upper:	7.0 Vol %

Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)
---	-------------------

Density:	Not determined.
Relative density:	Not determined.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information:	No further relevant information available.

10 Stability and Reactivity

Reactivity: No further relevant information available.

Chemical stability:
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicology Information

Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

Primary irritant effect:
On the skin: Irritant to skin and mucous membranes.

On the eye: No irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Irritant

Carcinogenic categories
IARC (International Agency for Research on Cancer)

108-88-3	toluene	3
	Xylene, Mixed Isomers	3

NTP (National Toxicology Program)

None of the ingredients are listed.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium
OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological Information

Toxicity:**Aquatic toxicity:** No further relevant information available.**Persistence and degradability:** No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential:** No further relevant information available.**Mobility in soil:** No further relevant information available.**Additional ecological information:****General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects:** No further relevant information available.

13 Disposal Considerations

Uncleaned packagings:**Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

UN-Number

DOT, ADR, IMDG, IATA

UN1993

UN proper shipping name

DOT

Flammable liquids, n.o.s.

ADR

1993 Flammable liquids, n.o.s.

IMDG, IATA

FLAMMABLE LIQUID, N.O.S.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Transport hazard class(es)	
DOT	
	
Class	3 Flammable liquids
ADR, IMDG, IATA	
	
Class	3 Flammable liquids
Packing group	
DOT, ADR, IMDG, IATA	II
Environmental hazards	Not applicable.
Special precautions for user:	Warning: Flammable liquids
EMS Number:	F-E, <u>S-E</u>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S., 3, II

15 Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture
SARA

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

108-88-3 toluene

TSCA (Toxic Substances Control Act):

129698-94-8 Acrylic Copolymer

108-88-3 toluene

Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium
Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

108-88-3 toluene

Carcinogenic categories
EPA (Environmental Protection Agency)

108-88-3 toluene

II

Xylene, Mixed Isomers

I

TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

Xylene, Mixed Isomers

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms


GHS02



GHS06



GHS07



GHS08

Signal word Danger

Hazard-determining components of labeling:

Xylene, Mixed Isomers

toluene

Hazard statements

Highly flammable liquid and vapor.

Toxic in contact with skin.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Wear protective gloves / protective clothing.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

This information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of the material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

Department issuing SDS: Regulatory Department

Contact: Phone 800-442-3573

Date of preparation / last revision 11/17/2016

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

SAFETY DATA SHEET

In Accordance with ISO/DIS 11014

Review Date 09/01/2022

Supersedes Date: 11/17/2016

Revision Date 09/01/2022

Product Name: ClearMount Mounting Medium

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Copyright © 2019-2021 SLMP, LLC, DBA StatLab Medical Products. All Rights Reserved.

No part of these pages may be used for any purpose other than personal use. Therefore, reproduction, modification, storage in a retrieval system or retransmission, in any form or by any means, for reasons other than personal use, is strictly prohibited without prior written permission.

US
