

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Treosin™

Product Code: SL93-16; SL93-1

Intended Use of the Product

Biological Stains. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

StatLab Medical Products

2090 Commerce Drive

McKinney, TX 75069

800-442-3573

www.statlab.com

Emergency Telephone Number

Emergency Number : CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International)

Non-transport 800-225-8867 (USA)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flammable Liquid 2 H225

Eye Irritation 2A H319

Specific Target Organ Toxicity - Single Exposure 1 H370

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

H370 - Causes damage to organs.

Precautionary Statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof ventilating, lighting, electrical equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe vapors, spray, mist.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective clothing, protective gloves.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307+P311 - If exposed: Call a poison center/doctor.

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide, water spray, fog to extinguish.

P403+P235+P405 - Store in a well-ventilated place. Keep cool. Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards Not available

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Ethyl alcohol	(CAS No) 64-17-5	68	Flammable Liquid 2, H225 Eye Irritation 2A, H319 Aquatic Acute 3, H402
Isopropyl alcohol	(CAS No) 67-63-0	4	Flammable Liquid 2, H225 Eye Irritation 2A, H319 Specific Target Organ Toxicity - Single Exposure 3, H336
Methyl alcohol	(CAS No) 67-56-1	4	Flammable Liquid 2, H225 Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:vapour), H331 Specific Target Organ Toxicity - Single Exposure 1, H370
Spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, 2',4',5',7'-tetrabromo-3',6'-dihydroxy-, disodium salt	(CAS No) 17372-87-1	< 1	Eye Irritation 2A, H319
C.I. Acid Orange 10	(CAS No) 1936-15-8	< 1	Skin Irritation 2, H315 Eye Irritation 2A, H319 Specific Target Organ Toxicity - Single Exposure 3, H335
Acid fuchsine	(CAS No) 3244-88-0	< 1	Skin Irritation 2, H315 Eye Irritation 2A, H319 Specific Target Organ Toxicity - Single Exposure 3, H335
Acetic acid	(CAS No) 64-19-7	< 1	Flammable Liquid 3, H226 Skin Corrosion 1A, H314 Eye Damage 1, H318 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Assure fresh air breathing. Call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes damage to organs. Irritation to eyes, skin and respiratory tract.

Inhalation: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.

Skin Contact: May cause skin irritation.

Eye Contact: May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Ingestion: Harmful if swallowed. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide, water spray, fog.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Use only non-sparking tools. Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Biological Stains. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Acetic acid (64-19-7)		
Mexico	OEL TWA (mg/m ³)	25 mg/m ³
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m ³)	37 mg/m ³
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	25 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	25 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	37 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Alberta	OEL STEL (mg/m ³)	37 mg/m ³
Alberta	OEL STEL (ppm)	15 ppm
Alberta	OEL TWA (mg/m ³)	25 mg/m ³
Alberta	OEL TWA (ppm)	10 ppm
British Columbia	OEL STEL (ppm)	15 ppm
British Columbia	OEL TWA (ppm)	10 ppm
Manitoba	OEL STEL (ppm)	15 ppm
Manitoba	OEL TWA (ppm)	10 ppm
New Brunswick	OEL STEL (mg/m ³)	37 mg/m ³
New Brunswick	OEL STEL (ppm)	15 ppm
New Brunswick	OEL TWA (mg/m ³)	25 mg/m ³
New Brunswick	OEL TWA (ppm)	10 ppm
Newfoundland & Labrador	OEL STEL (ppm)	15 ppm
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm
Nova Scotia	OEL STEL (ppm)	15 ppm
Nova Scotia	OEL TWA (ppm)	10 ppm
Nunavut	OEL STEL (mg/m ³)	39 mg/m ³
Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (mg/m ³)	26 mg/m ³
Nunavut	OEL TWA (ppm)	10 ppm
Northwest Territories	OEL STEL (mg/m ³)	39 mg/m ³
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (mg/m ³)	26 mg/m ³
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	15 ppm
Prince Edward Island	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m ³)	37 mg/m ³
Québec	VECD (ppm)	15 ppm

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Québec	VEMP (mg/m ³)	25 mg/m ³
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m ³)	43 mg/m ³
Yukon	OEL STEL (ppm)	25 ppm
Yukon	OEL TWA (mg/m ³)	25 mg/m ³
Yukon	OEL TWA (ppm)	10 ppm

Ethyl alcohol (64-17-5)		
Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	1000 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
Alberta	OEL TWA (mg/m ³)	1880 mg/m ³
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL STEL (ppm)	1000 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
New Brunswick	OEL TWA (mg/m ³)	1880 mg/m ³
New Brunswick	OEL TWA (ppm)	1000 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Nunavut	OEL STEL (mg/m ³)	2355 mg/m ³
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (mg/m ³)	1884 mg/m ³
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (mg/m ³)	2355 mg/m ³
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (mg/m ³)	1884 mg/m ³
Northwest Territories	OEL TWA (ppm)	1000 ppm
Ontario	OEL STEL (ppm)	1000 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1880 mg/m ³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Yukon	OEL STEL (mg/m ³)	1900 mg/m ³
Yukon	OEL STEL (ppm)	1000 ppm
Yukon	OEL TWA (mg/m ³)	1900 mg/m ³
Yukon	OEL TWA (ppm)	1000 ppm

Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m ³)	980 mg/m ³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m ³)	1225 mg/m ³
Mexico	OEL STEL (ppm)	500 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	984 mg/m ³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m ³)	492 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	1230 mg/m ³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m ³)	983 mg/m ³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	1228 mg/m ³
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (mg/m ³)	983 mg/m ³
Nunavut	OEL TWA (ppm)	400 ppm
Northwest Territories	OEL STEL (mg/m ³)	1228 mg/m ³
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (mg/m ³)	983 mg/m ³
Northwest Territories	OEL TWA (ppm)	400 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m ³)	985 mg/m ³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	1225 mg/m ³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m ³)	980 mg/m ³
Yukon	OEL TWA (ppm)	400 ppm
Methyl alcohol (67-56-1)		
Mexico	OEL TWA (mg/m ³)	260 mg/m ³
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m ³)	310 mg/m ³
Mexico	OEL STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
Alberta	OEL STEL (mg/m ³)	328 mg/m ³
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m ³)	262 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	328 mg/m ³
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (mg/m ³)	262 mg/m ³
New Brunswick	OEL TWA (ppm)	200 ppm
Newfoundland & Labrador	OEL STEL (ppm)	250 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	328 mg/m ³
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (mg/m ³)	262 mg/m ³
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (mg/m ³)	328 mg/m ³
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (mg/m ³)	262 mg/m ³
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	328 mg/m ³
Québec	VECD (ppm)	250 ppm
Québec	VEMP (mg/m ³)	262 mg/m ³
Québec	VEMP (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	310 mg/m ³
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m ³)	260 mg/m ³
Yukon	OEL TWA (ppm)	200 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Alarm detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Ensure all national/local regulations are observed. Local exhaust and general ventilation must be adequate to meet exposure standards. Site-specific risk assessments should be conducted to determine the appropriate exposure control measures. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal Protective Equipment: Full protective flameproof clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: When effective engineering controls are not feasible, appropriate respirators shall be used. Personal Protective Equipment must be selected by trained personnel, taking into account the type of hazardous materials it should protect from, the nature of the work, the expected exposure, and the facial characteristics of the wearers; proper fit is of paramount importance. Ensure the respiratory protection program meets the requirements of OSHA 29 CFR 1910.134.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Red-Orange
Odor	: Ethanol Odor
Odor Threshold	: Not available
pH	: 6.55 - 6.85
Evaporation Rate	: Not available
Melting/Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density / Specific Gravity	: 0.79 - 0.88 (water = 1)
Solubility	: Soluble in water.
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin Corrosion/Irritation: Not classified (pH: 6.55 - 6.85)

Serious Eye Damage/Irritation: Causes serious eye irritation. (pH: 6.55 - 6.85)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Causes damage to organs.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Symptoms/Injuries After Ingestion: Harmful if swallowed. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Acetic acid (64-19-7)	
LD50 Oral Rat	3310 mg/kg
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
Isopropyl alcohol (67-63-0)	
LD50 Oral Rat	4710 mg/kg
LD50 Dermal Rabbit	4059 mg/kg
LC50 Inhalation Rat	72600 mg/m ³ (Exposure time: 4 h)
Methyl alcohol (67-56-1)	
LC50 Inhalation Rat	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.00 mg/kg body weight
ATE US (dermal)	300.00 mg/kg body weight
ATE US (vapors)	3.00 mg/l/4h
Spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, 2',4',5',7'-tetrabromo-3',6'-dihydroxy-, disodium salt (17372-87-1)	
IARC Group	3
Isopropyl alcohol (67-63-0)	
IARC Group	3
C.I. Acid Orange 10 (1936-15-8)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

Acetic acid (64-19-7)	
LC50 Fish 1	79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Ethyl alcohol (64-17-5)	
LC50 Fish 1	12.0 - 16.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
Methyl alcohol (67-56-1)	
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability

Ethyl alcohol (64-17-5)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Treosin™	
Bioaccumulative Potential	Not expected to bioaccumulate.
Acetic acid (64-19-7)	
Log Pow	-0.31 (at 20 °C)
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)
Methyl alcohol (67-56-1)	
BCF Fish 1	< 10
Log Pow	-0.77

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

Note: This product meets a limited quantity exemption. The shipping information below only applies when the product is shipped in quantities greater than 1 L (0.3 Gallons). Therefore, when the product is shipped in pint form (16 oz), the below does not apply.

14.1. UN Number

UN-No.(DOT) : 1987
DOT NA no. : UN1987

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Alcohols, n.o.s.
Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard Classes
Hazard Labels (DOT) : 3 - Flammable liquid



Packing Group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102)	: 172 - This entry includes alcohol mixtures containing up to 5% petroleum products. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
14.3. Additional Information	
Emergency Response Guide (ERG) Number	: 128
Transport by Sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
MFAG-No	: 171
Air Transport	
DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75)	: 60 L

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Treosin™	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
Spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, 2',4',5',7'-tetrabromo-3',6'-dihydroxy-, disodium salt (17372-87-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Acetic acid (64-19-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)
Methyl alcohol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1.0 %
C.I. Acid Orange 10 (1936-15-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Acid fuchsine (3244-88-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Ethyl alcohol (64-17-5)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Methyl alcohol (67-56-1)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Acetic acid (64-19-7)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Louisiana - Reportable Quantity List for Pollutants U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2 RTK - U.S. - Massachusetts - Right To Know List U.S. - Massachusetts - Toxics Use Reduction Act U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Michigan - Polluting Materials List U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - North Carolina - Control of Toxic Air Pollutants U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	

U.S. - Washington - Permissible Exposure Limits - STELS
 U.S. - Washington - Permissible Exposure Limits - TWAs
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Ethyl alcohol (64-17-5)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
 U.S. - Idaho - Occupational Exposure Limits - TWAs
 U.S. - Maine - Chemicals of High Concern
 U.S. - Massachusetts - Allowable Ambient Limits (AALs)
 U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
 RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Minnesota - Chemicals of High Concern
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New Jersey - Special Health Hazards Substances List
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELS
 U.S. - Washington - Permissible Exposure Limits - TWAs

Isopropyl alcohol (67-63-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
 U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
 U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
 U.S. - Connecticut - Volatile Substances
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
 U.S. - Idaho - Occupational Exposure Limits - TWAs
 RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Massachusetts - Toxics Use Reduction Act

U.S. - Michigan - Occupational Exposure Limits - STELs
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - STELs
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
 U.S. - New Jersey - Environmental Hazardous Substances List
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New Jersey - Special Health Hazards Substances List
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
 U.S. - Tennessee - Occupational Exposure Limits - STELs
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - STELs
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
 U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
 U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
 U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
 U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
 U.S. - Connecticut - Volatile Substances
 U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
 U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
 U.S. - Idaho - Occupational Exposure Limits - TWAs
 U.S. - Illinois - Toxic Air Contaminants
 U.S. - Louisiana - Reportable Quantity List for Pollutants
 U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
 U.S. - Maine - Chemicals of High Concern
 U.S. - Massachusetts - Allowable Ambient Limits (AALs)
 U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
 RTK - U.S. - Massachusetts - Right To Know List
 U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)

U.S. - Massachusetts - Toxics Use Reduction Act
 U.S. - Michigan - Occupational Exposure Limits - Skin Designations
 U.S. - Michigan - Occupational Exposure Limits - STELs
 U.S. - Michigan - Occupational Exposure Limits - TWAs
 U.S. - Michigan - Polluting Materials List
 U.S. - Minnesota - Chemicals of High Concern
 U.S. - Minnesota - Groundwater Health Risk Limits
 U.S. - Minnesota - Hazardous Substance List
 U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
 U.S. - Minnesota - Permissible Exposure Limits - STELs
 U.S. - Minnesota - Permissible Exposure Limits - TWAs
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
 U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
 U.S. - New Jersey - Environmental Hazardous Substances List
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - New Jersey - Special Health Hazards Substances List
 U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
 U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
 U.S. - New York - Occupational Exposure Limits - Skin Designations
 U.S. - New York - Occupational Exposure Limits - TWAs
 U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
 U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
 U.S. - Oregon - Permissible Exposure Limits - TWAs
 U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
 RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List
 U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
 U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
 U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
 U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
 U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
 U.S. - Tennessee - Occupational Exposure Limits - STELs
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - Skin Designations
 U.S. - Vermont - Permissible Exposure Limits - STELs
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
 U.S. - Washington - Permissible Exposure Limits - Skin Designations
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Canadian Regulations


Treosin™

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



Spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, 2',4',5',7'-tetrabromo-3',6'-dihydroxy-, disodium salt (17372-87-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Acetic acid (64-19-7)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Class B Division 3 - Combustible Liquid
Class E - Corrosive Material

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Class B Division 2 - Flammable Liquid
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

C.I. Acid Orange 10 (1936-15-8)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Acid fuchsine (3244-88-0)

Listed on the Canadian DSL (Domestic Substances List)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 04/17/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Toxicity 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Toxicity 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Toxicity 3 (Oral)	Acute toxicity (oral) Category 3


Treosin™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Damage 1	Serious eye damage/eye irritation Category 1
Eye Irritation 2A	Serious eye damage/eye irritation Category 2A
Flammable Liquid 2	Flammable liquids Category 2
Flammable Liquid 3	Flammable liquids Category 3
Skin Corrosion 1A	Skin corrosion/irritation Category 1A
Skin Irritation 2	Skin corrosion/irritation Category 2
Specific Target Organ Toxicity - Single Exposure 1	Specific target organ toxicity (single exposure) Category 1
Specific Target Organ Toxicity - Single Exposure 3	Specific target organ toxicity (single exposure) Category 3
Specific Target Organ Toxicity - Single Exposure 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H402	Harmful to aquatic life

- NFPA Health Hazard** : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard** : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health** : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability** : 3 Serious Hazard
- Physical** : 0 Minimal Hazard

Party Responsible for the Preparation of This Document

StatLab Medical Products

Phone Number: 800-442-3573

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS